

Solar Foldable **Hanging Light**



Instructions

Information on solar lamp

The lamp is a solar-operated accent and marking lamp. Operate the lamp only vertically. It is weatherproof and should be operated in direct sunlight. The rechargeable batteries are partially charged at the time of delivery. Full power will be available after about three days of operation on sunny days. This enables optimum southward orientation. Press the orange button to activate the light. When the battery is fully charged, the lamp will illuminate for up to 6-8 hours. In winter and during unfavorable weather conditions this time can be shorter. 5V USB adaptor can charge it

Lamp will keep on if you do not switch it off.

Functions:

Press the orange button above lamp, its function will sequentially change as below:

- 1. High Brightness 2.Low Brightness
- 3.Strong Brightness
- 4.Fast SOS flash 5.Low SOS flash
- 6.OFF

Maintenance and care

Accumulations of dirt or snow on the solar cell can reduce the duration of the illumination. Do not use solvents for cleaning and do not apply pressure to the solar module.



Troubleshooting:

If the lamp does not work despite having followed these instructions, then please check the following:


- Charging under sun or other strong light for a few hours
- Charging with 5V USB for a few hours.
- Press the button 1sec each to check if it works.
- Check the solar cell for damage.
- Make sure that the lamp is not in the shade during the day.

Lamps are not toys. Children frequently do not recognize the dangers associated with the improper handling of electric appliances or their packaging. Therefore, you should keep them away from children. If you give this lamp to someone else, always include the operating instructions.

Environmental protection

Dispose of the rechargeable battery at a suitable collection point for batteries.

LED DAYLIGHT IP44 18650 L 3,7V DC 2x1200mAh



Specfication

- Product Size: H14.5 * D28cm
- 2pcs*3.7V 18650-1200mAh lithium battery
- Solar Panel: 5.5V 0.8W polycrystalline drip panel
- Material: ABS.
- Working Mode: Strong weak flash SOS
- Working Time: 6-8 hours
- IP: 44









